



Model Thyonet Broadband Quad Wireless Radio - Achilles G400

Frequencies **2.4GHz Band:**
2400-2497MHz (*)

Standard Compliance IEEE 802.11b/g

Access Method TDD (CSMA/CA)



Channel Bandwidth 20 or 40 MHz (Selectable by Software)

Modulation technique DSSS/OFDM (BPSK,QPSK, 16-QAM, 64-QAM)




Output Power **2.4GHz Band:**
26dBm@6-24Mbps
21dBm@54Mbps

Receive Sensitivity **2.4GHz Band:**
-97dBm@1Mbps
-94dBm@6Mbps
-74dBm@54Mbps

Certificates FCC ID SWX-SR2
CE
RoHS





RF Operational Modes	<ul style="list-style-type: none"> Access Point (bridge or router function) WDS (bridge or router function) Repeater (bridge or router function) AP Client (bridge or router function) Station (bridge or router function) 	
Advanced Wireless Features	<ul style="list-style-type: none"> Tx Power and Tx Rate Antenna Selection ACK Timeout WMM - Wireless QoS Mac Address Spoofing Hide SSID and Stealth Mode Best Channel Selection and Country Code Selection DFS/TPC (Dynamic Frequency Selection / Transmit Power Control) Compression, Bursting, Fast Frames 802.11h Full Support Antenna Alignment (Site Survey / Link Quality / Signal Level) 	
Network Advanced Features	<ul style="list-style-type: none"> Transparent Bridging Layer 2 (Mac Address) Forwarding Layer 3 (IP Address) Forwarding Static Routing DHCP Server and Client PPPoE Client/PPTP Client Vlan (802.1Q) Support Advance Statistics Graphical User Interface Monitor Utils (Ping and Trace Route) 	
Firewall - NAT	<ul style="list-style-type: none"> Input/Output Interface Source IP/Subnet Port(s) Source Mac Destination IP/Subnet Protocol (ICMP, TCP, etc) Connection State(New, Established, etc) 	
Security Features	<ul style="list-style-type: none"> Access Control List WEP 64/128 WPA1/WPA2 with TKIP & AES ciphers 	
QoS - Bandwidth Management	<ul style="list-style-type: none"> Committed Information Rate (CIR) Peak Information Rate (PIR) Committed Burst Size (CBS) Excess Burst Size (EBS) Based in : <ul style="list-style-type: none"> - Input/Output Interface - Source IP/Subnet - Source Port(s) - Source Mac - Destination IP/Subnet - Destination Port(s) - Destination Mac - Protocol (FTP, ICMP, TCP, etc) - Application (Peer to Peer, EDonkey, Kazza, IRC, etc) 	
Hot Spot Features	<ul style="list-style-type: none"> WAN, LAN, DHCP, Firewall - NAT QoS - Bandwidth Management Wireless Radius Client UAM Authentication, Mac Address Authentication Walled Garden Advertisement Sites Log in Page Customization Users Info, Radius Statistics 	
Administration Tools	<ul style="list-style-type: none"> SNMP Agent NTP Agent HTTP Server SSH 	